



# CG165-75

PRO-SERIES II DRYING TUMBLER



2500 State Road 44 • Oshkosh, WI 54904  
 920.231.8222 • FAX 920.231.4666  
[www.continentalgirbau.com](http://www.continentalgirbau.com)

Capacity <i>lbs (kg)</i>	up to 175
Cylinder Diameter <i>inch (mm)</i>	50.75 (1289)
Cylinder Depth <i>inch (mm)</i>	42.5 (1080)
Cylinder Volume <i>cu ft (dm<sup>3</sup>)</i>	49.8 (1.41)
Net Weight <i>lbs (kg)</i>	
Gas	1575 (716)
Steam	1675 (761)
Crated Weight <i>lbs (kg)</i>	
Gas	1667 (756)
Steam	1776 (806)
Machine Width <i>inch (mm)</i>	53.12 (1349)
Machine Depth <i>inch (mm)</i>	68.85 (1749)
Machine Height <i>inch (mm)</i>	94 (2388)
Door Opening <i>inch (mm)</i>	26.89 (683)
Floor to Door <i>inch (mm)</i>	33.86 (860)
Shipping Dimensions <i>inch (mm)</i>	55.63 x 73.75 x 99
	(1413 x 1873 x 2515)
Reversing Motor Power <i>Hp (kW)</i>	
Cylinder	3/4 (0.56)
Fan	3 (2.24)
Exhaust Diameter <i>inch (mm)</i>	12 (300)
Exhaust Air Flow <i>cfm (l/s)</i>	2450 (1156)
Gas Connection <i>inch (mm)</i>	1 NPT (25.4)
Gas Heating <i>BTU/h (Kcal/h)</i>	395,000 (99,538)
Steam Connection <i>inch (mm)</i>	3/4 NPT (19)
Condensate Outlet Connection <i>inch (mm)</i>	1 NPT (25.4)
Steam Heating <i>BTU/h (kW)</i>	
at 100 PSI (6.9 bar)	648,000 (189.9)
BHP Consumption <i>BHP</i>	
at 100 PSI (6.9 bar)	18.8
Available Voltages/Wire Conductor/Amp (Rev Amp)	200-208/240/60/3, 3W + G, (13.5)
	440/60/3, 3W + G, (6.4)
	460-480/60/3, 3W + G, (6.7)

\* Specifications subject to change without notice or obligation. Call Continental Girbau Inc for dimensions not shown or for clarification.

