




2500 State Road 44 • Oshkosh, WI 54904  
 920.231.8222 • FAX 920.231.4666  
[www.continentalgirbau.com](http://www.continentalgirbau.com)



# EH040

ON-PREMISE LAUNDRY E-SERIES 40-POUND CAPACITY  
 HIGH-PERFORMANCE WASHER-EXTRACTOR

|   |   |
|---|---|
| Capacity <i>lbs (kg)</i>                        | 40 (17.3)                               |
| Cylinder Diameter <i>inch (mm)</i>              | 27.6 (700)                              |
| Cylinder Depth <i>inch (mm)</i>                 | 17.7 (450)                              |
| Cylinder Volume <i>cu ft (dm<sup>3</sup>)</i>   | 6.1 (173)                               |
| Net Weight <i>lbs (kg)</i>                      | 1049 (476)                              |
| Crated Weight <i>lbs (kg)</i>                   | 1091 (495)                              |
| Machine Width <i>inch (mm)</i>                  | 34.2 (868)                              |
| Machine Depth <i>inch (mm)</i>                  | 37.9 (962)                              |
| Machine Height <i>inch (mm)</i>                 | 55.3 (1404)                             |
| Door Opening <i>inch (mm)</i>                   | 16.8 (426)                              |
| Floor to Door <i>inch (mm)</i>                  | 20.3 (515)                              |
| Shipping Dimensions <i>inch (mm)</i><br>(WxDxH) | 35.3 x 40 x 61.6<br>(897 x 1017 x 1565) |
| Washing Speeds <i>rpm</i>                       |   |
| Logi Control                                    | 44                                      |
| Inteli Control                                  | 17/23/30/37/44                          |
| Spin Speeds <i>rpm</i>                          | 100/375/570/750/950                     |
| G-force   | 3.92/55/127/220/354                     |
| Static Force Transmitted <i>lbs (kg)</i>        | 1237 (561)                              |
| Dynamic Force Transmitted <i>lbs (kg)</i>       | 212 (96)                                |
| Frequency of Dynamic Force <i>Hz</i>            | 15.8                                    |
| Available Voltages/Wire Conductor/Amp           |   |
| Hot Water (standard)                            | 208-240/60/1, 2W + G, 10 Amp            |
| Electric Auxiliary Heat (optional)              | 208/60/1, 2W + G, 45 Amp                |
| Electric Auxiliary Heat (optional)              | 240/60/1, 2W + G, 60 Amp                |
| Electric Auxiliary Heat (optional)              | 208/60/3, 2W + G, 40 Amp                |
| Electric Auxiliary Heat (optional)              | 240/60/3, 3W + G, 50 Amp                |
| Steam Auxiliary Heat (optional)                 | 240/60/1, 2W + G, 10 Amp                |
| Modified Energy Factor (MEF)*                   | 1.96                                    |
| Water Consumption Factor (WCF)*                 | 5.04                                    |
| Drain Diameter <i>inch (mm)</i>                 | 3 (76)                                  |
| Water Inlets <i>inch (mm)</i>                   | 2 @ 3/4 (19)                            |
| Recommended Water Pressure <i>PSI (bar)</i>     | 30-60 (2-4)                             |
| Water Flow <i>gal/min (l/min)</i>               | 16 (60)                                 |
| Steam Connection <i>inch (mm)</i>               | 1/2 (12.7)                              |
| Steam Pressure (optional) <i>PSI (bar)</i>      | 29-87 (2-6)                             |
| Steam Flow (optional) <i>lbs/h (kg/h)</i>       | 176 (80)                                |
| Total Power <i>kW</i>                           | 1.3                                     |
| Electric Heating Power (optional) <i>kW</i>     |   |
| Single Phase 240V                               | 10.6                                    |
| Three Phase 240V                                | 15.6                                    |

\* Modified Energy Factor (MEF) measured in cubic feet per kilowatt-hour per cycle. Water Consumption Factor (WCF) measured in gallons per cycle per cubic feet. MEF and WCF statistics are according to DOE test results report by Intertek, an independent testing laboratory, dated February 27, 2007.

\*\* Specifications subject to change without notice or obligation. Call Continental Girbau Inc for dimensions not shown or for clarification.

