

# EHO40

## ON-PREMISE E-SERIES SOFT-MOUNT WASHER-EXTRACTOR

PRODUCT SPECS	
Capacity <i>lbs</i>	40
Cylinder Diameter <i>inch</i>	27.6
Cylinder Depth <i>inch</i>	17.7
Cylinder Volume <i>cu ft</i>	6.1
Net Weight <i>lbs</i>	1049
Crated Weight <i>lbs</i>	1091
Machine Dimensions <i>inch</i> WxDxH	34.2 x 37.9 x 55.3
Door Opening <i>inch</i>	16.8
Floor to Door <i>inch</i>	20.3
Shipping Dimensions <i>inch</i> WxDxH	35.3 x 40 x 61.6
Washing Speed <i>rpm</i> Logi Control Inteli Control	44 17/23/30/37/44
Spin Speeds <i>rpm</i>	100/375/570/750/950
G-force	3.92/55/127/220/354
Static Force Transmitted <i>lbs</i>	1237
Dynamic Force Transmitted <i>lbs</i>	212
Frequency of Dynamic Force <i>Hz</i>	15.8
Available Voltages/Wire Conductor/Amp	
Hot Water (standard)	208-240/60/1, 2W+G, 10
Electric Auxiliary Heat (optional)	208/60/1, 2W+G, 45
Electric Auxiliary Heat (optional)	240/60/1, 2W+G, 60
Electric Auxiliary Heat (optional)	208/60/3, 2W+G, 40
Electric Auxiliary Heat (optional)	240/60/3, 3W+G, 50
Steam Auxiliary Heat (optional)	240/60/1, 2W+G, 10
Modified Energy Factor (MEF)	1.96
Water Consumption Factor (WCF)	5.04
Drain Diameter <i>inch</i>	3
Water Inlets <i>inch</i>	2 @ 3/4
Recommended Water Pressure <i>PSI</i>	30-60
Water Flow <i>gal/min</i>	16
Steam Connection <i>inch</i>	1/2
Steam Pressure (optional) <i>PSI</i>	29-87
Steam Flow (optional) <i>lbs/h</i>	176
Total Power <i>kW</i>	1.3
Electrical Heating Power (optional) <i>kW</i>	
Single Phase 240V	10.6
Three Phase 240V	15.6

\* Specifications subject to change without notice or obligation. Contact Continental Girbau at (800) 256-1073 for dimensions not shown or for clarification.

\* Modified Energy Factor (MEF) measured in cubic feet per kilowatt-hour per cycle. Water Consumption Factor (WCF) measured in gallons per cycle per cubic feet. MEF and WCF statistics are according to DOE test results report by Intertek, an independent testing laboratory, dated February 27, 2007.

